Zero Air generator for GC

Part Number : See Reverse

Intura ZA

Service Kit · See Revers



Description

Designed to supply clean, dry, hydrocarbon-free air for detector gas to your GC, Intura ZA has a fully integrated oil-free air compressor delivering a self contained, plug and play solution for GC detector gas.

PEAK's uniquely designed CAT chamber optimizes the path of compressed air as it enters the CAT chamber, ensuring increased contact time to eliminate ambient CH₄ levels, from 100ppm to <0.05ppm in outlet air. This efficient design operates at a lower temperature, reducing power consumption and heat output.

Coming in a compact design, Intura Zero Air helps to minimize the total footprint required in the lab along with providing the flexibility to add or remove other Intura modules as your requirements evolve over time.

Applications

- Flame detector support gas
- Atomic absorption
- Pyrolizers





Key Features

- S Zero Air generator with integrated air compressor
- O Up to 15L/min
- Adjustable pressure up to 100psi
- Highly efficient CAT chamber
- Low power consumption, reducing power draw and operational carbon footprint
- Compact design, saving valuable lab bench space
- In-field upgrade to N2|ZA possible
- High-quality touchscreen for operation, reminders and alerts
- Auxiliary air outlet enabling support of Intura N2 or autosamplers, pyrolizers and other laboratory applications requiring clean, dry air
- Advanced oil-free compressor
- 12-month comprehensive warranty, with the option to extend up to 5 years

Technical Specifications	Intura ZA 1500	Intura ZA 3500	Intura ZA 7000	Intura ZA 15000		
Max Flow Rate	1500 cc/min	3500 cc/min	7000 cc/min	15000 cc/min		
Output Pressure	100psi / 6.9 bar					
Dewpoint	-35°C / -31°F					
Purity (CH ₄)	<0.5 ppm NOx / SOx / Phthalate free					
Power Consumption	616 w					
Electrical Requirements	~100-120V, 60Hz / ~220-240V, 50/60Hz					
Dimensions (H X W x D)	496 x 330 x 586 mm / 19.5 x 12.9 x 23.1 in					
Weight	40kg / 88lbs					
Noise Level	<60dB(A)					
Max altitude	3000m					
Warranty	12 months (with option to extend up to 5 years)					

Ordering Information						
Part Number (120v)	3305331-1-01	3305331-1-02	3305331-1-03	3305331-1-04		
Part Number (230v)	3305331-2-01	3305331-2-02	3305331-2-03	3305331-2-04		
Annual Service						
Standard Maintenance Plan	www.peakscientific.com/ordering					
Complete Maintenance Plan						
Extended Warranty						

PEAK Protected][™]

Peak Scientific gas generators define the benchmark in reliability, convenience and performance in laboratories around the world, and come backed by a 12 month warranty, with the option to extend up to 5 years. Beyond this period however you can ensure that your investment continues to be **[Protected]** by our comprehensive generator care cover.

Our world-class aftercare support packages deliver a program of scheduled preventative maintenance whilst giving you the reassurance of instant access to worldwide technical support and priority on-site response in the untimely event of a breakdown.



(주) **구정이엔티** 서울시 구로구 디지털로31길 20, 1103호(구로동, 에이스테크노타워 5차) Tel. 02)3281-2374 Email. marketing@goojung.com homepage. www.goojung.com

